

Point of Use

Water heaters



Under sink




Above sink






Ratings and dimensions

Capacity (L)	Output (W)	Voltage (V)	Heat-up time at 60°C ($\Delta t=20^{\circ}\text{C}$)	Heat-up time at 60°C ($\Delta t=50^{\circ}\text{C}$)	Energy Consumption (kWh/24h at 65°C)
10 above sink	1600	230 (220-240)	10	24	0,48
15 compact above sink	1600	230 (220-240)	14	35	0,58
30	2000	230 (220-240)	23	57	0.76
50	2000	230 (220-240)	38	96	1.13
10 under sink	2000	230 (220-240)	8	18	0,63
15 compact under sink	2000	230 (220-240)	9	23	0,66



Capacity (L)	H	Ø	Dimensions (mm)				Flange opening (Ø)	Net Weight (kg)
			B	C	D	E		
10 above sink	456	255	166	290	64	262	72 mm	8
15 compact above sink	399	338	163	236	81	345	72 mm	9
30	623	338	160	463	81	345	72 mm	12.5
50	918	338	168	750	81	345	72 mm	17
10 under sink	456	255	238	218	64	262	72 mm	8
15 compact under sink	399	338	235	164	81	345	72 mm	9



(For other standards, consult us)