atlantic

FRENCH BRAND
SINCE 1968

Expert

USER-FRIENDLY WATER HEATER WITH FRONTAL KNOB AND VERY ACCURATE CONTROLS





+ PRODUCT

COMFORT

- Frontal control knob for the most accurate temperature control
- 2000 W heating element
- Flat chromed thermometer

USER-FRIENDLINESS

- IP 24 - full compliance with European standards for electrical safety and user protection
- Plug*
- Heating light indicator



QUALITY - DURABILITY

- Long tank lifetime thanks to O'Pro exclusive anti-corrosive system
- Magnesium anode for strengthened tank protection
- New generation diamond-quality enamel (glass-lined inner tank)
- Pressure relief valve
- Dielectric union
- Specific lip gasket to avoid corrosion around flange

SAVINGS

- High-precision bulb thermostat with integrated security for accurate controls
- High-efficiency water inlet
- CFC-free high-density insulation for more energy savings


ELECTRIC WATER HEATER — 50 TO 100 L (VERTICAL WALL-MOUNTED)

				
Model available**	More hot water	Frontal control knob	Tank protection	Copper heating element

*Depending on models - **Model types: A: Vertical wall-mounted / B: Horizontal wall-mounted / C: Floor-standing

FRENCH BRAND
SINCE 1968

Expert




1 External thermometer
2 Diamond-quality enamel (glass-lined inner tank)
3 Optimised stainless steel outlet pipe
4 Magnesium anode
5 Sheathed immersion heating element
6 Inlet diffuser
7 O'Pro anti-corrosive system
8 High-density polyurethane foam 0% CFC
9 Frontal control knob
10 Dielectric union
11 Thermostat


O'PRO Ohmic protection


+50% TANK LIFETIME

O'Pro exclusive anti-corrosive system balances out the electrical potential of the tank and immersion heating element. Thus, the magnesium anode life is considerably increased and protection against corrosion is reinforced.



INSTALLATION DIMENSIONS





TECHNICAL DATA

CAPACITY (L)	OUTPUT (W)	VOLTAGE (V)	ENERGY CONSUMPTION (kWh/24h AT 65°C)	HEAT-UP TIME AT 60°C (ΔT=50°C)
50	2000	230 (220/240)	0.95	1h25
80	2000	230 (220/240)	1.35	2h34
100	2000	230 (220/240)	1.70	3h05

DIMENSIONS

CAPACITY (L)	DIMENSIONS (mm)							FLANGE OPENING (Ø) mm	NET WEIGHT (Kg)	ERP ENERGY CLASS	PROFILE
	A	B	C	D	E	F	G				
50	629	433	395	451	158	300	239	72	15	C	M
80	876	433	605	451	158	300	239	72	21	C	L
100	1038	433	755	451	158	300	239	72	24	C	L

CE - EAC - IP 24

Atlantic International a simplified joint stock company with €2 000 007, 17 rue Croix Fauchet - RCS Orléans B 390 284 693 - No contractual pictures – August 2018 - www.L2R.fr