atlantic

FRENCH BRAND
SINCE 1968

Vertigo Steatite Wi-Fi

SMART, STYLISH AND SPACE-SAVING WATER HEATER THAT BRINGS YOU OPTIMUM THERMAL COMFORT

Models 30 to 100 (Multi-position installation)

BENEFITS

- Space-saving solution due to flat design (less than 30 cm depth)
- Fast heating thanks to double-tank structure
- Steatite heating element protected by a sleeve for limited scaling and easy maintenance
- Connectivity & remote control via the Cozytouch application
- Energy savings: Eco+ mode, Absence mode, Energy consumption follow-up

PREMIUM · ENERGY SAVINGS · ErP Compliant B

Available colors: White & Silver

EASY PROGRAMMING WITH DIGITAL CONTROL PANEL

Waterdrop LED Indicator: Level of hot water ready to use

Boost: Increase hot water production to meet unforeseen needs

Absence mode: Anti-frost position (7 °C)

Manual mode: Selection of required hot water quantity

Eco+ mode: Automatic operation according to consumer's daily habits

WI-FI CONNECTIVITY & REMOTE CONTROL

With Cozytouch App you can:

- Manage your water heater from everywhere
- Monitor your energy consumption
- Tailor your home comfort to your needs
- Switch off water heater when you are out

Cozytouch

Download the APP for free

Download on the App Store

GET IT ON Google Play

atlantic

FRENCH BRAND
SINCE 1968

Vertigo Steatite Wi-Fi

Models 30 to 100 (Multi-position installation)

PROVEN QUALITY WITH STEATITE TECHNOLOGY

1 **DIAMOND QUALITY GLASS LINING** for long life and reliability

2 High-density, 0% CFC polyurethane foam

3 **MAGNESIUM ANODE X2** for protection against corrosion

4 Inlet diffuser

5 Optimised stainless steel outlet pipes

6 **ELECTRONIC REGULATION** for temperature control accuracy



x2 Steatite TECHNOLOGY

DRY STEATITE HEATING ELEMENT



Adapted to aggressive, highly mineralised and desalinated water.
Its protective enamel-coated steel sleeve makes maintenance easy, and there is no need ever to drain the tank to replace it.

EASY MAINTENANCE

EASY INSTALLATION

• Wall mounted plates and drilling template available on the packaging

Installation dimensions

Model	Dimensions (mm)				Net weight (kg)
	H	A	B(5)	C	
30(1)	593	452	280	141	19.5
50(2)	766	609	500	157	24.5
80(3)	1090	973	700	117	32.5
100(4)	1301	1184	800	117	37.5



Technical data

Model	Number of users	Maximum power output: exit tank (W)	Power output: entry tank (W)	Voltage (V)	Total heat-up time ΔT=50°C	Heat-up time: exit tank	Energy consumption (kWh/24 h at 65°C)	ErP energy class	Profile
30(1)		1000	1000	220-240	1h27	0h44	0.28	B	S
50(2)		2250	1000	220-240	1h46	0h33	0.69	B	M
80(3)		2250	1000	220-240	2h52	0h53	1.01	B	M
100(4)		2250	1000	220-240	3h32	1h05	1.11	B	M

(1) ErP capacity is 25 L (2) ErP capacity is 40 L (3) ErP capacity is 65 L (4) ErP capacity is 80 L

CE EAC IP 24

www.atlantic-comfort.com

Atlantic International a simplified joint stock company with €2 000 007, 17 rue Croix Fauchet - RCS Orléans B 390 284 693 - No contractual pictures – October 2021 - www.L2R.fr